

gSKIN[®] KIT U-Value Kit

FEATURES

- Calibrated Plug-and-Play solution
- Measurement of U-Value (W/(m²K)), heat flux (W/m²), and 2 temperatures (°C)
- Compatible with standards ISO 9869 and ASTM C1046 / ASTM C1155
- Stores up to 2 million data points
- Battery lifetime > 1 month
- High sensitivity thermal detectors
- Read-out software included
- Compact design
- USB interface



gSKIN[®]-XO 67 7C




DLOG-4231



Transport box

Product Name	gSKIN[®] KIT-2615C
Article Number	A-163479
gSKIN [®] KIT includes ^a	Sensor: gSKIN [®] -XO 67 7C (30mm x 30mm) Logger: DLOG-4231 incl. 2 temperature sensors Software Mounting Tape
Heat Flux Range Min / Max [W/m ²]	±35 ^d
Heat Flux Resolution [W/m ²]	<0.11
Min. Sensor Sensitivity ^b (S) [μV/(W/m ²)]	15
Temperature Sensor Accuracy [°C]	±0.5 (-10...+65 °C) ±2.0 (-55...+125 °C)
Logger Dimensions (l x w x h) [mm x mm x mm]	52 x 20 x 15
Measurement Frequency	1/sec to 1/h
Bit Resolution [bits]	12
Data Storage Capacity [# measurements]	>2'000'000
Battery Lifetime ^c [days]	>30 (rechargeable)
Computer Interface	USB
Software	Installation-SW sent by email / via download link
Operating System	Windows 2000 / XP / Vista / 7 / 8
Operation Modes	Live display / Data logger
Operating Temperature Range Min/Max [°C]	-50 / 150 (-20 / 65 for Logger)
Calibration Temperature Range Min/Max [°C]	-30 / 70
Calibration Accuracy ^b [±%]	3
Temperature Sensor 1 / 2 Cable Length [m]	5.0 / 1.0
Heat Flux Sensor / Logger Cable Length [m]	1.0 / 0.5 (with connectors)



^a For more details consult the datasheets of the individual products.

^b Sensor calibration data already loaded onto logger for simple and

fast plug-and-play measurements.

^c At lowest measurement frequency (2/d).

^d Heat Flux Range up to +/- 400 [W/m²] available on request

Datasheet V4.0, © Copyright greenTEG AG, 2019 All Rights Reserved